

SECTION 08800 - GLAZING

A. SUMMARY

1. Glazing required for the following:
 - a. Window units.
 - b. Vision lites.
 - c. Glazed curtain walls.
 - d. Entrances and other doors.
 - e. Storefront construction.
 - f. Skylights.
 - g. Sloped glazing systems.

B. QUALITY ASSURANCE

1. Mockups [**for each glass product**].
2. Preconstruction compatibility and adhesion testing.

C. WARRANTY

1. Deteriorated Coated Glass: Not less than five years.
2. Deteriorated Laminated Glass: Not less than five years.
3. Deteriorated Insulating Glass: Not less than 10 years.

D. MATERIALS

1. Float Glass: [**Clear**] [**Tinted**].
2. Heat-Treated Float Glass: [**Uncoated, clear float**] [**Uncoated, tinted float**] [**Coated, clear float**] [**Coated, tinted float**].
3. Ceramic-coated spandrel glass.
4. Coated Monolithic Glass: [**Pyrolytically**] [**Sputter**] coated.
5. Wired Glass: [**Polished**] [**Patterned**].
6. [**Tempered**] patterned glass.
7. Laminated Glass: [**Polyvinyl butyral sheet**] [**Urethane acrylate resin**] interlayer.

8. Sealed insulating-glass units.
9. Fire-Resistive Glazing: [**Ceramic**] [**Gel-filled, dual-glazed units**] [**Gel-filled, triple-glazed units**].
10. Elastomeric sealant.
11. Glazing Tapes: [**Back-bedding mastic type**] [**Expanded cellular type**].
12. Glazing Gaskets: [**Lock strip**] [**Dense compression**] [**Soft compression**].

E. GLASS SCHEDULE

1. <**Insert requirements for each type of glass.**>

END OF SECTION 08800